

VIDEO INSPECTION SCOPE

TECHNICAL DATA

FEATURES

- High definition inspection scope detects and diagnoses problems without direct physical or visual access
- Provides real time imaging only
- High resolution 2.4" colour TFT LCD monitor with display resolution of 480(W)X 234(H)
- 17mm imager head with 1m flexible gooseneck retains configured shape and is waterproof
- Gooseneck is expandable up to 30' with optional cable extensions
- Four high visibility LED lights provide illumination in dark locations with brightness control
- 2X zoom button and 180° mirror rotation button
- Operates on 4 x 1.5V "AA" batteries
- Includes video borescope, imager head, magnet, hook and mirror attachments, and batteries



SPECIFICATIONS

TFT LCD Size: 2.4"
Display Resolution: 480 x 234
Active Area: 48mm x 35.6mm
Viewing Distance: 5.9 to 9.8" (15 to 25cm)
Viewing Angle: 0 to 180°
Sensor Size: 1/4" CMOS
Sensor Pixels: 300,000
Max. Resolution: 640 x 480
Max. Frames: 30 fps
Depth of Field (DOF): 10mm to infinity
Camera Diameter: 0.66" (17mm); Length: 39" (1m)
Power Supply: 4 x 1.5V AA batteries

ORDERING INFORMATION

R8100 Video Inspection Scope
 BS-C6 6' Cable Extension
 BS-15-9C3 9mm Replacement Camera Head
 w/ 3' Cable