

HVAC COMBO KIT

TECHNICAL DATA

BUY AS A KIT & SAVE!

The REED-HVAC-KIT combination kit consists of all of the tools you require for your heating, ventilation and air conditioning needs. All items may be purchased separately as required.

FEATURES

REED R2100 Thermal Imaging Camera

- IR Resolution: 160 x 120 pixels
- Thermal sensitivity (NETD) of <80mK
- Interchangeable lenses with automatic lens recognition
- 3.5" colour TFT LCD capacitive touch screen
- Automatic image capture at a frequency of 50 Hz
- Temperature Range: -20 to 400°C (-4 to 752°F)

REED R3002 Digital Manometer

- Measures gauge and differential pressures from 0 to 5.000 psi
- 11 selectable units of measure: psi, inH₂O, bar, mbar, kPa, inHg, mmHg, ozin², ftH₂O, cmH₂O, kgcm²
- Max/Min/Avg record with time stamp

REED R5100 Non-contact AC Voltage Detector

- Detects for the presence of AC voltage without contact
- Signals the presence of voltage with an LED light and audible buzzer
- AC Voltage Range: 90 to 1000V

REED GD-3300 Combustible Gas Detector

- Detects a wide variety of gases, including some toxic gases and nuisance vapors
- Audible (variable tick rate) and visible indications help to pinpoint leak sources
- Adjustable sensitivity helps to eliminate background gas concentrations in contaminated environments

REED R6020 Temperature/Humidity Data Logger

- Stores up to 16,000 temperature and 16,000 humidity readings
- User selectable measurement rate from 2 s to 24 h
- Humidity Range: 0 to 100% RH
- Temperature Range: -40 to 70°C (-40 to 158°F)



ORDERING INFORMATION

REED-HVAC-KIT	HVAC Combo Kit
CERTIIR4	R2100 Calibration Certificate
CERTIMTF4	R3002 Calibration Certificate
CERTIGM1	GD-3300 Calibration Certificate
CERTITH1	R6020 Calibration Certificate