

The Right Source. The Right Solutions.



THERMO-HYGROMETER/ DATA LOGGER

TECHNICAL DATA

FEATURES

- Measures relative humidity as well as temperature with a type J/type K thermocouple thermometer
- Also measures dew point and wet bulb temperatures
- Automatic temperature compensation
- · Easy to read LCD with backlight
- Data hold and Max/Min record
- Real time data logger with integral 2GB SD memory card (OPTIONAL)
- Just plug the SD card into the computer and it downloads directly to EXCEL
- RS-232 and USB computer interface
- Auto or manual power off

SPECIFICATIONS

Humidity Range: 5% to 95% RH

Resolution: 0.1% RH

Accuracy: ≥70% RH: ± (3% reading + 1% RH)

< 70% RH: ± 3% RH

Temperature Range: 0 to 50°C (32 to 122°F)

Resolution: 0.1°C/°F **Accuracy:** ±0.8°C (±1.5°F)

Dew Point Range: -25.3 to 48.9°C (13.5 to 120.1°F)

Resolution: 0.1°C/°F

Wet Bulb Range: -21.6 to 50.0°C (-6.9 to 122.0°F)

Resolution: 0.1°C/°F

Type K Temp.Range: -100.0 to 1300.0°C (-148.0 to 2372°F)

Resolution: 0.1°C/°F

Accuracy: $\pm (0.4\% + 0.5^{\circ}\text{C}/+1^{\circ}\text{F})$

Type J Temp.Range: -100.0 to 1200.0°C (-148.0 to 2192°F)

Resolution: 0.1°C/°F

Accuracy: $\pm (0.4\% + 0.5^{\circ}\text{C}/+1^{\circ}\text{F})$

Power Supply: $6 \times 1.5 \text{V UM}3/AA$ batteries Dimensions: $177 \times 68 \times 45 \text{mm}$ (7.0 x 2.7 x 1.9")

Weight: 515g (1.13 lb)



ORDERING INFORMATION

SD-3007 Ther	mo-Hygrometer/Data Logger
TP-01 Type	e K Thermocouple Wire Probe
SD-2GB	2GB SD Memory Card
USB-01	USB Cable
CA-05A	Soft Carrying Case
SW-U801-WIN	Data Acquisition Software
BS-6	Tripod
AP-9VA-110V	AC adapter
CERTITH1	NIST Calibration Certificate
SD-3007-NIST	. Thermo-Hygrometer & NIST